

# 2012 Buell 1190 RS For Sale

22,000 €

## QUICK SPEC

Make	Buell
Model	1190 RS
Version	
Registration Year	2012
Mileage	POA Km - POA Mi
Limited Edition	One of only 100 Units Produced
Exterior Colour	Racing
Category	Ultra-light American Superbike
Make	Buell Racing

## TECHNICAL SPECIFICATIONS

### ENGINE

Cylinders Type - V-twin with a 73-degree cylinder angle  
Engine Details - Rotax 1125 racing engine  
Displacement (cc) : 1,1 litre (1,125 cc / 68,7 cu in)  
Fuel System - Injection. Dual 61 mm down draft throttle bodies, DDFI III fuel injection  
Starter - Electric  
Valves per Cylinder - 4

### PERFORMANCE

Power - 173 bhp / 175 PS / 131 kW @ 11,500 rpm  
Torque - 131,5 Nm / 97 ft lbs @ 9,750 rpm  
Max Speed - 250 km/h (155 mph)  
Acceleration - 0-100 km/h // 0- 62 mph in 2,7 secs  
Exhaust system - Tuned, tri-pass resonance chamber with integral helmholtz tuning and mass-

### TRANSMISSION

Gearbox - Manual  
Gears - 6 Speed  
Transmission Type - Chain

### CHASIS & SUSPENSION

Frame Type - aluminum-beam chassis that doubles as the fuel tank  
Front Suspension - 47 mm Ohlins inverted forks  
Rear Suspension - Ohlins coil-over monoshock with external piggyback reservoir

## BRAKE & WHEELS

Front Brakes - Single disc. ZTL2-type brake, 8-piston, 4 pads, fixed caliper

Front Brakes Diameter - 375 mm (14.8 inches)

Rear Brakes - Single disc. Two-piston, direct mount caliper

Rear Brakes Diameter : 240 mm (9.4 inches)

Front Tyre - 120/70-ZR17

Rear Tyre - 180/55-ZR17

## MEASURES & CAPACITIES

Dry Weight - 174 kg (384 pounds)

Fuel capacity - 20 litres (5,3 gallons)

## CATALOGUE ESSAY

The Buell 1190 RS t is a Ultra-light American Superbike Motorcycle from Buell. Its Engine V-twin with a 73-degree cylinder angle Rotax 1125 racing engine with 1,1 litre (1,125 cc / 68,7 cu in) displacement, produces 173 bhp / 175 PS / 131 kW @ 11,500 rpm, and maximum torque of 131,5 Nm / 97 ft lbs @ 9,750 rpm. The Buell 1190 RS equip a aluminum-beam chassis that doubles as the fuel tank Chassis, 47 mm Ohlins inverted forks Front Suspension and Ohlins coil-over monoshock with external piggyback reservoir Rear Suspension. The Buell 1190 RS 375 mm (14.8 inches) Single disc. ZTL2-type brake, 8-piston, 4 pads, fixed caliper and 240 mm (9.4 inches) Single disc. Two-piston, direct mount caliper Rear Brakes stops the Bike ,The claimed dry at the kerb is 174 kg (384 pounds) is said to be able to manage a top speed of 250 km/h (155 mph) and 0-100 km/h // 0- 62 mph in 2.7 secs.

- \$45,000 original retail
- Carbon Fiber Production racer
- Fresh out of the crate
- All carbon fiber
- Less than 100 built
- Last 2012 available for sale, recently uncrated from the factory crate
- An original factory AMA Pro Race Bike
- Factory upgraded from the \$45,000 1190RS, this bike had over \$100K added to the build expenses
- Raced extensively in the AMA pro Race Series
-

