

# 1958 Ariel Square Mark II Four For Sale

28,600 €

## QUICK SPEC

Make	Ariel
Model	4G Square Four
Version	Mark II
Registration Year	1958
Mileage	21,400 km - 13,300 mi
Limited Edition	One of only Units Produced
Exterior Colour	Two Tone
Category	Allround

## TECHNICAL SPECIFICATIONS

### ENGINE

Cylinders Type - Square four cylinder  
Engine Details - Double twin cylinder arranged as a square  
Displacement (cc) : 995 CC / 60.71 cu in  
Fuel System - Carburettor. SU MC2 carburettor with air cleaner  
Ignition -  
Starter - Kick  
Valves per Cylinder - 2

### PERFORMANCE

Power - 43,4 Hp / 44 PS / 32,8 kW @ 5,500 rpm  
Torque - TBA Nm / TBA ft lbs @ 0,000 rpm  
Max Speed - 160 km/h (100 mph)  
Acceleration - 0-100 km/h // 0- 62 mph in 0,0 secs

### TRANSMISSION

Gearbox - Manual  
Gears - 4 Speed  
Transmission Type - Chain

### CHASIS & SUSPENSION

Frame Type - Full cradle  
Front Suspension - Oil Damped Telescopic  
Rear Suspension - Plunger-link spring

## BRAKE & WHEELS

Front Brakes - Expanding brake (drum brake).

Front Brakes Diameter - 203 mm (8.0 inches)

Rear Brakes - Expanding brake (drum brake).

Rear Brakes Diameter : 178 mm (7.0 inches)

Front Tyre - 3.25-19

Rear Tyre - 4.00-18

## MEASURES & CAPACITIES

Dry Weight - 197.3 kg (435.0 pounds)

Fuel capacity - 18.93 litres (5.00 gallons)

## CATALOGUE ESSAY

The Ariel Square Mark II is a Allround motorcycle from Ariel, Designed by Edward Turner. Its Engine Type Square four cylinder, Double twin cylinder arranged as a square with a displacement of 995 CC / 60.71 cu in capacity. The Ariel Square Mark II has an output of 43,4 Hp / 44 PS / 32,8 kW @ 5,500 rpm rpm and maximum torque of 000 Nm / 00,0 ft lbs / 00,0 Kgm @ 10,000 rpm. The Ariel Square Mark II Uses a Full cradle Chassis, Oil damped telescopic Front Suspension and Plunger-link spring Rear Suspension. The 203 mm (8.0 inches) Expanding brake front Brakes and 178 mm (7.0 inches) Expanding brake rear Brakes stops the Bike ,The claimed dry at the kerb is 197.3 kg (435.0 pounds) is said to be able to manage a top speed of 160 km/h (100 mph)

